

## ISO 3601 - 1 ORINGONE extended version

Cord CS (thickness)		ISO 3601-1			
		ORINGONE extended		ISO standard version	
mm	inch	mm	inch	mm	inch
2,62	0,103	± 0,08	± .003	± 0,08	± .003
3,00	0,118	± 0,09	± .003	± 0,09	± .003
3,53	0,139	± 0,10	± .004	± 0,10	± .004
4,00	0,157	± 0,10	± .004	± 0,10	± .004
4,50	0,177	± 0,10	± .004	± 0,10	± .004
5,00	0,197	± 0,13	± .005	± 0,13	± .005
5,33	0,210	± 0,13	± .005	± 0,13	± .005
5,50	0,217	± 0,15	± .006	± 0,15	± .006
5,70	0,224	± 0,15	± .006	± 0,15	± .006
6,00	0,236	± 0,15	± .006	± 0,15	± .006
6,35	0,250	± 0,15	± .006	± 0,15	± .006
6,50	0,256	± 0,15	± .006	± 0,15	± .006
7,00	0,276	± 0,15	± .006	± 0,15	± .006
7,50	0,295	± 0,15	± .007	± 0,15	± .006
8,00	0,315	± 0,18	± .007	± 0,15	± .006
8,40	0,331	± 0,18	± .007	± 0,15	± .006
9,00	0,354	± 0,20	± .008	NO TOLERANCE VALUES PROVIDED	
9,50	0,374	± 0,20	± .008		
10,00	0,394	± 0,20	± .008		
10,82	0,426	± 0,20	± .008		
11,00	0,433	± 0,20	± .008		
12,00	0,472	± 0,22	± .009	NO TOLERANCE VALUES PROVIDED	
12,70	0,500	± 0,23	± .009		
13,00	0,512	± 0,23	± .010		
14,00	0,551	± 0,25	± .011		
14,40	0,567	± 0,26	± .011		
15,00	0,591	± 0,27	± .011	NO TOLERANCE VALUES PROVIDED	
16,00	0,630	± 0,29	± .011		
17,00	0,669	± 0,30	± .012		
18,00	0,709	± 0,32	± .013		
19,00	0,748	± 0,34	± .013		
20,00	0,787	± 0,36	± .014	NO TOLERANCE VALUES PROVIDED	
22,00	0,866	± 0,39	± .015		
24,00	0,945	± 0,43	± .017		
25,00	0,984	± 0,45	± .017		
26,00	1,024	± 0,47	± .017		
28,00	1,102	± 0,50	± .019	NO TOLERANCE VALUES PROVIDED	
30,00	1,181	± 0,54	± .021		
40,00	1,575	± 0,72	± .028		

